



METRIC TEST POINTS - M16x2.00

These plugs form part of the HSP Test Equipment range which is designed to be complementary to and interchangeable with similar equipment from other manufacturers. Test points are installed into the hydraulic system hardware and can be used with Pressure Test Probe Equipment. The equipment is used to obtain random pressure checks during service and fault finding. Probes may be connected and disconnected at full system pressure without fluid loss or ingress of dirt.


BSPP THREAD	HEIGHT (MM)	D (MM)	B (MM)	WEIGHT (KG)	PART NUMBER
1/8" BSPP	48.40	17.00	10.00	0.06	HSP2000-A
1/4" BSPP	52.00	19.00	12.70	0.07	HSP2000-B
3/8" BSPP	52.50	22.00	12.70	0.08	HSP2000-C



UNF THREAD	HEIGHT (MM)	D (MM)	B (MM)	WEIGHT (KG)	PART NUMBER
7/16" UNF	49.50	17.00	9.15	0.07	HSP2000-D
9/16" UNF	50.22	19.00	10.00	0.07	HSP2000-E



THREAD / 'O' RING	HEIGHT (MM)	D (MM)	B (MM)	WEIGHT (KG)	PART NUMBER
M10 X 1.00	48.90	17.00	10.50	0.06	HSP2000-M
M12 X 1.50	52.65	19.00	12.00	0.07	HSP2000-P
M10 X 1.25	48.90	17.00	10.50	0.06	HSP2000-Q
M14 x 1.5	52.65	19.00	12.00	0.08	HSP2000-J
1/8" BSPP	52.00	19.00	12.00	0.07	HSP2000-A-F
1/4" BSPP	52.00	19.00	12.00	0.07	HSP2000-B-F
1/4" BSPP	53.55	19.00	12.00	0.07	HSP2000-B-E



HSP2000-B-E has an encapsulated seal to DIN3852 From E Specifications

BSPT /NPTF THREAD	HEIGHT (MM)	D (MM)	B (MM)	WEIGHT (KG)	PART NUMBER
1/8" BSPT	48.40	17.00	10.00	0.06	HSP2000-F
1/4" NPFT	54.30	19.00	14.50	0.07	HSP2000-H
1/8" NPTF	48.40	17.00	10.00	0.06	HSP2000-K

